



## *T2-C2*

### **Table-Top ConveyORIZED Cleaner**

**MODEL : 1610C-1212-1SPP-50**

**Application:** Aqueous Spray Parts Cleaning

**Machine Type:** 16" x 10" Pass-Through  
Conveyor Parts Washer(Aqueous)

**Machine Foot Print:** 52" Tall x 52" Long x 36"  
Wide (Including Table)



### **4-Directional Spray Chamber, Single Stage, Heated**

Pump Make	Penguin P-1.5
Pump Style	CPVC Vertical Shaft Seal-Less Centrifugal
Pump Motor	1.5 HP, 1Ø, 3450 RPM, TEFC
Pump Pressure	40-50 PSI
Pump Volume	30 GPM
Spray Pattern	1" Manifold, 6 Spray Bars(2 Top, Bottom & Sides)
Nozzles	36 Acetal Nozzles
Nozzle Type (Top/Sides)	Flat Fan 95° Angle
Nozzle Type (Bottom)	Flat Fan 95°
Heat Control	Protec, DE20, Digital Thermostat w/ Teflon RTD Sensor and Liquid Level Safety Interlock
Heat Input	Type 304 SS, 9kW, Tubular Screw Plug Heaters (Max. Temp. 160° F)
Sump Volume	40 Gallons
Sump Drain	1" CPVC w/ Manual Ball Valve
Sump Overflow Drain	1" CPVC
Water Fill Inlet	1/2" PVC Manual Valve (Auto-Fill Option Available)
Pump Sump Filter Screen	12" x 16" Fine Mesh Polypropylene
Spray Chamber Debris Tray	6" x 42" x 4" Tray w/ 20 x 20 Mesh SS Screen
Effective Spray Area	16" Wide x 10" High x 18" D.O.T.

*Call us today for the solution to your fabrication requirements. 1-888-733-2832*



**HPI Processes, Inc.**  
1030 Revenue Dr. Telford, PA 18969  
Phone 888-733-2832 Fax 215-799-0459



### **SYSTEM CONSTRUCTION**

Material (Main Body)	1/2" & 3/4" White Stress-Relieved Polypropylene
Material (Top Access Lid)	1/2" Blue PVC (Textured Exterior)
Material (Spray Cover)	1/4" Clear Polycarbonate
Material (Plumbing)	All CPVC for Solution, PVC for Water Fill
Conveyor Frame	3/4" UHMW-Polyethylene

### **CONVEYOR SYSTEM**

Conveyor Dimensions	16" Wide x 50" Overall Length @36" Loading Height
Load & Unload Areas	Both 12" Length
Conveyor Material	304 SS, 1" x 1" Openings, Flat Wire Belt
Belt Flow Direction	Left to Right (Right to Left Available, No Charge)
Conveyor Speed Range	0-8 Feet Per Minute, Var. DC Speed Control
Conveyor Drive	1/8 HP, 180VDC Permanent Magnet Gearmotor

### **ELECTRICAL SYSTEM**

Power	230 VAC, 1Ø, 60 Hz, 30 Amp
Control	Man. Operator SW & Relay Logic 110VAC Controls
Control Panel	Polypropylene NEMA 4X Enclosure
Safety Disconnect	Not Included (Optional Provision)
Circuit Protection	Individual Circuit Fuses & Motor Overload Relays
Emergency Shut-Off	Operator Mushroom Head PB (Load End Only)
Operator Interface	All NEMA 4X Operator Switches and Indicators

### **OPTIONAL FEATURES FOR BASE MACHINE**

Sump Auto-Fill	Automatic Water Level Control
Lid Safety Switch	Shuts Down Machine if Lid is Opened
Lid Gas Springs	Aid in Opening and Prevent Accidental Closure
Oil Skimmer	10" Ø Motor Driven Disc w/Dual Scraper Drain Outlet
Table Frame w/ Casters	Polypropylene Drip Tray, Capped Powder Coated Steel Frame w/ Corrosion Resistant Swivel Casters

*Call us today for the solution to your fabrication requirements. 1-888-733-2832*